

G-18 Line

ANSI

Ideal for industrial and heavy cleaning operations; system designed for heat dissipation that prevents burns on the pieces.



GRADE AVAILABILITY

024 036 050 060 080

EXTRA COARSE / COARSE / MEDIUM
HEAVY GRINDING

Backing Vulcanized fiber of high resistance of 0.030".

Mineral Zirconia Alumina.

Grades ANSI: 024, 036, 050 to 080.

Coating Closed.

Ideal



METAL



NONFERROUS
METAL

Shapes



DISCS

Applications



FIBER
BACKING



USE
SAFETY
EQUIPMENT



EMERY
FOR
ABRASIVE
DISCS



PLASTIC
BACKING

Applications

- For heavy and intermediate polishing tasks.
- For sanding hardened, alloyed and stainless steel.
- For weld bead removal.
- To make weld distribution as efficient and symmetrical as possible and use the least amount of material as possible.
- Inoxidizable alloys are applied in the pharmaceutical, food and nuclear industries. That is why high quality is of utmost importance so the resulting work does not affect corrosion resistance or health of the surface.
- Inoxidizable alloys are applied in the pharmaceutical, food and nuclear industries. That is why high quality is of utmost importance so the resulting work does not affect corrosion resistance or health of the surface.

Characteristics

- Excellent performance in operations that require high operating pressures.
- Aggressive action, superior performance and long life.
- High hardness and resistance, has greater rigidity and maximum resistance.
- Heat dissipation system prevents burns on the pieces.

FANDELI®

www.fandeli.com